Massey Ferguson®

9520 Rotary Combine AGCM95200EHC16501 AND UP

SERVICE MANUAL 4283559M1

CONTENTS

GENERAL INFORMATION	01
SPECIFICATIONS	02
ENGINE WORKSHOP MANUAL	03 <i>A</i>
ENGINE - DRIVES, COOLING AND FUEL	
MATERIAL HANDLING	04
MATERIAL DISCHARGE	05
REAR AXLE	06
THRESHING AND SEPARATING	
FRONT AXLE	08
HYDRAULICS	09
CAB AND HVAC	
WIRING DIAGRAMS	
ELECTRICAL	11E
DIAGNOSTICS	12
GRAIN HEADER INSERT	13
CORN HEADER INSERT	14
DRAPER HEADER INSERT	15

Massey Ferguson®

9520 Rotary Combine

SERVICE MANUAL 4283559M1

01 - General Information

Contents

Safety Alert Symbol	,	24.4
Safety Messages		
Informational Messages	(ノ -
Safety Signs	() -Z
A Word To The Operator	(JT-3
Operator Manual	(J1-4
Prepare For Operation		
Operation	()1-5
General Information	(J1-5
PPE (Personal Protection Equipment)	(J1-6
Seat Instructions		
Shield and Guards		
Exhaust Warning		
Flying Debris		
Handrails		
Travel On Public Roads		
Maintenance		
General Information		
Fire Prevention and First Aid	01	1-12
Checking for High Pressure Leaks	01	1-13
Engine Safety		
Adding Fuel		
Diesel Exhaust Fluid Safety		
Battery Safety	01	1-16
Tire Safety		
Accumulator Safety		
Safety Equipment		
Hazard Lamps		
Beacon Lamps		
Backup Alarm		
Parking Brake		
Fire Extinguisher		
Header Lift Cylinder Stop		
Machine Main Components		
How A Combine Works	01	1_20
Cutting and Feeding		
Threshing and Separating		
Cleaning		
Combine Identification	0	1-2 I 1 22
Serial Number Plate Location		
Serial Number Definition		
Headers		
Disposal	U1	1-25

Contents

Disposal of Waste 0			
Disposal of Machine 0			
Lubrication and Maintenance 0			
Lubricants 0			
Service Procedures			
Lubricating and Maintaining the Combine 0			
Lubrication and Maintenance Charts 0			
New Machine 0			
10 Hours or Daily 0			
50 Hours or Weekly 0			
Every 100 Hours or Monthly 0			
Every 250 Hours			
Every 500 Hours)1	-3	31
Every 1000 hours)1	-3	32
Every 1200 Hours)1	-3	32
Grease Fitting Locations)1	-3	33
Left-hand Side of Combine 0) 1	-3	33
Right-hand Side of Combine0			
Auto Lube0			
Auto Lube Intervals 0			
Auto Lube Diagnosis			
Engine Platform0			
Engine Platform Ladder			
Engine Compartment			
Engine			
Type of Engine Oil			
Oil Additives			
Checking Oil Level			
Changing Engine Oil and Filters			
Fuel System			
Fuel Vent Breather			
Engine Fuel Filter			
Selective Catalytic Reduction System			
Diesel Exhaust Fluid Filter) I	-D) / - O
Draining the DEF storage tank and Metering Module			
Engine Air Cleaner			
Outer Filter Element			
Inner Filter Element			
Engine Cooling System			
Coolant System Monitoring			
Monitor Warnings			
Anti-Freeze Type 0			
Coolant Change Period	J 1	-6	30
Engine Cooling System Coolant			
Checking Coolant Level			
Radiator 0			
Draining System 0			
Filling System0			
Rotor Gearbox 0			
Transmission)1	-6	<u>3</u> 4
Checking and Changing Lubricant 0			
Brakes			
Master Cylinder Oil Reservoir)1	-6	35
Bleeding Brake System 0			
Final Drive)1	-6	36
Tires and Wheels 0)1	-6	37
Tire Pressure0) 1	-6	37
Dual Tires 0			
Maintenance of Tires			
Removing Wheel from Combine 0			
Wheel Installation			
Tire Dimensions			
Drive Belts			

Contents

Banded Drive Belt			
Maintenance of Belts			
Belt Changing Guides			
Belt Sheave Alignment			
Belt Run In Procedure			
Belt Troubleshooting	0	11-	-/6
Belt Problem and Wear Guide			
Roller Chains			
Care of Chains			
Drive Chain Sprocket and Idler Alignment			
Drive Chain Sprocket and Idler Alignment Drive Chain Elongation and Sprocket Wear			
Normal Tooth Wear	. 0	11	90
Not Normal Tooth Wear			
Worn Chain on New Sprockets			
Drive Chain Service Tips			
Chain Replacement			
Cleaning and Lubricating Chains	. 0	1-	-97
Drive Chain Lubrication			
Drive Chain Lubricants			
Good Drive Chain Lubrication	. 0	11-	-99
Roller Chain Drive Troubleshooting Guide	01	-1	100
Speed of Components			
Drives Listing and Specifications	01	-1	104
Hydraulics			
General	01	-1	106
Checking Oil Level	01	-1	107
Hydraulic Oil Filter	01	-1	107
Changing Hydraulic Oil	01	-1	108
Removing Air From Hydraulic System	01	-1	111
Hydraulic Pump	01	-1	112
Steering Priority Valve			
Main Hydraulic Control Valve			
Unloader Auger Engagement Valve			
Hydraulic Oil Cooler			
Air Conditioning System			
Compressor			
Condenser			
Receiver-Drier			
Cab Filters			
Cab Filter - Primary			
Cab Filter - SecondaryRecirculation Filter			
Air Filter Cleaning Procedure			
Windshield Washer Reservoir			
Cleaning Windshield			
Storage Preparation			
Combine			
Engine			
Preparation For Use After Storage			
Combine			
Engine			
Emissions Warranty			
Torque Charts			
Standard Bolt Markings and Torque Values			
Metric Capscrew Markings and Torque Values			
Special Torque Requirement			
Metric Conversions			
Fractions, Decimals, and Millimeters Conversion Chart	01	-1	132
Decimal Equivalents of 8ths, 16ths, 32nds, and 64ths	01	-1	137
Decimal Equivalents Of Letter Size Drills	01	-1	138
Decimal Equivalents of Number Size Drills	01	-1	139

Contents

	ap Drill Sizes - S.A.E. & Metric	
Α	merican Standard Pipe Thread and Tap Drill Sizes	01-145
Ε	lectrical Formulas	01-145
	Amperes (Current Flow)	01-145
	Volts (Electromotive Force)	01-145
	Ohms (Resistance)	01-146
	Watts	01-146
	Horsepower	01-146
В	elt Speed Calculation Formulas	01-146
G	Seometrical Formulas	01-146
	Circumference of a Circle	
	Area of a Circle	
	Volume of a Cylinder	01-146
	Volume of a Sphere	01-146
	Area of a Triangle	
M	letric to Imperial and Imperial to Metric Conversion Factors	01-147
	Measures of Temperature	
	Measures of Power	01-147
	Measures of Pressure	01-147
	Measures of Length	01-147
	Measures of Area	01-148
	Measures of Volume (Dry)	01-148
	Measures of Volume (Liquid)	01-149
	Measures of Mass (Weight)	
	Measures of Effort (Torque)	01-150
	Reference Tables	
NΓ)FX	01-155

SAFETY ALERT SYMBOL

FIG. 1: The safety alert symbol means ATTENTION! BECOME ALERT! YOUR SAFETY IS INVOLVED!

Look for the safety alert symbol both in this manual and on safety signs on this machine. The safety alert symbol will direct your attention to information that involves your safety and the safety of others.



FIG. 1

SAFETY MESSAGES

FIG. 2: The words DANGER, WARNING or CAUTION are used with the safety alert symbol. Learn to recognize these safety alerts and follow the recommended precautions and safety practices.



DANGER: Indicates an imminently hazardous situation that, if not avoided, will result in DEATH OR VERY SERIOUS INJURY.



WARNING: Indicates a potentially hazardous situation that, if not avoided, could result in DEATH OR SERIOUS INJURY.



CAUTION: Indicates a potentially hazardous situation that, if not avoided, may result in MINOR INJURY.

INFORMATIONAL MESSAGES

The words IMPORTANT and NOTE are not related to personal safety, but are used to give additional information and tips for operating or servicing this equipment.

IMPORTANT: Identifies special instructions or procedures which, if not strictly observed, could result in damage to or destruction of the machine, process, or its surroundings.

NOTE: Identifies points of particular interest for more efficient and convenient repair or operation.



FIG. 2

SAFETY SIGNS



WARNING: Do not remove or obscure Danger, Warning or Caution signs. Replace any Danger, Warning or Caution signs that are not readable or are missing. Replacement signs are available from your dealer in the event of loss or damage. The actual location of the safety signs is illustrated at the end of this section.

Keep signs clean by wiping off regularly. Use a cleaning solution if necessary.

If parts have been replaced or a used machine has been purchased, make sure all safety signs are in the correct location and can be read. See Safety Sign Location in this section for illustrations.

Replace any safety signs that can not be read or are missing. Clean the machine surface thoroughly with a cleaning solution before replacing signs. Replacement safety signs are available from your dealer.

01-2 4283559M1

A WORD TO THE OPERATOR

FIG. 3: It is YOUR responsibility to read and understand the safety section in this manual and the manual for all attachments before operating this machine. Remember YOU are the key to safety. Good safety practices not only protect you, but also the people around you.

Study the features in this manual and make them a working part of your safety program. Keep in mind that this safety section is written only for this type of machine. Practice all other usual and customary safe working precautions, and above all REMEMBER - SAFETY IS YOUR RESPONSIBILITY. YOU CAN PREVENT SERIOUS INJURY OR DEATH.

This safety section is intended to point out some of the basic safety situations that may be encountered during the normal operation and maintenance of your machine. This section also suggests possible ways of dealing with these situations. This section is NOT a replacement for other safety practices featured in other sections of this manual.

Personal injury or death may result if these precautions are not followed.

Learn how to operate the machine and how to use the controls properly.

Do not let anyone operate the machine without instruction and training.

For your personal safety and the personal safety of others, follow all safety precautions and instructions found in the manuals and on safety signs affixed to the machine and all attachments. Use only approved attachments and equipment.

Make sure your machine has the correct equipment needed by the local regulations.



WARNING: An operator should not use alcohol or drugs which can affect their alertness or coordination. An operator on prescription or 'over the counter' drugs needs medical advice on whether or not they can properly operate machines.



CAUTION: If any attachments used on this equipment have a separate Operator Manual, see that manual for other important safety information.



CAUTION: See the engine Operation and Maintenance Manual for other important safety information.



CAUTION: See the combine Operator Manual for other important safety information.




FIG. 3

OPERATOR MANUAL

This manual covers general safety practices for this machine. The Operator Manual must always be kept with the machine.

Right-hand and left-hand, as used in this manual, are determined by facing the direction the machine will travel when in use.

The photos, illustrations, and data used in this manual were current at the time of printing, but due to possible in-line production changes, your machine can vary slightly in detail. The manufacturer reserves the right to redesign and change the machine as necessary without notification.



WARNING: In some of the illustrations and photos used in this manual, shields or guards may have been removed for clarity. Never operate the machine with any shields or guards removed. If the removal of shields or guards is necessary to make a repair, they MUST be replaced before operation.

FIG. 4: The Operator Manual is stored in the holder (1) on the machine. After using the Operator Manual, return the manual to the storage location.




FIG. 4

PREPARE FOR OPERATION

Read and understand all operating instructions and precautions in this manual before operating or servicing the machine.

Make sure you know and understand the positions and operations of all controls. Make certain all controls are in neutral and the parking brake is applied before starting the machine.

All equipment has a limit. Make sure you understand the speed, brakes, steering, stability, and load characteristics of this equipment before you start.

01-4 4283559M1

OPERATION

General Information

FIG. 5: When parking, park the machine on a solid level surface and lower the header to the ground. Put all controls in neutral and apply the parking brake. Stop the engine and take the key with you.



WARNING: Do not leave the machine unattended with the header raised. Lower the header fully before leaving the machine. A sudden loss of hydraulic pressure can cause the header to drop without warning.

Make sure the machine is in the proper operating condition according to the Operator Manual.

Always operate the machine with the control console turned on.

Do not dismount from moving machinery.

Stay off slopes too steep for operation.

Be aware of the size of the machine and have enough space available to allow for operation.

FIG. 6: Use extra care and reduce speed when operating on hillsides or near ditches or embankments especially with a full grain tank to avoid rollover. Travel speed must be such that complete control and machine stability is maintained at all times. Shift to a lower gear before descending a steep hill.

Regulate ground speed to field conditions, and maintain control at all times.

Do not dismount from moving machinery.

FIG. 7: Avoid contact with electrical power lines. Always put the grain tank unloader tube in the transport position and lower radio aerial before moving combine near electrical wires. Contact with electrical power lines can cause electrical shock, resulting in very serious injury or death.




FIG. 5




FIG. 6




FIG. 7

FIG. 8: Never allow anyone on any part of the combine or attachments except in the operator's seat and the instructional seat when the engine is running.

Do not to get on or off the combine while the combine is moving.



FIG. 8

FIG. 9: Always shut off the engine, shift the transmission to neutral, set parking brake and remove the start key before leaving the operator's station or before permitting anyone to inspect, clean, lubricate, adjust or repair any part of the combine or attachments unless specifically instructed otherwise in this manual. Never leave combine unattended while the engine is operating.



FIG. 9

PPE (Personal Protection Equipment)

FIG. 10: Wear all personal protective equipment (PPE) and protective clothing issued to you or called for by job conditions and country/local regulations. PPE includes, but is not limited to, equipment to protect eyes, lungs, ears, head, hands and feet when operating, servicing or repairing equipment.

Always keep hands, feet, hair, and clothing away from moving parts. Do not wear loose clothing, jewelry, watches, or other items that could entangle in moving parts. Tie up long hair that can also entangle in moving parts.




FIG. 10

01-6 4283559M1

Seat Instructions

FIG. 11: Securely fasten the seat belt before operating the machine. Always remain seated and have the seat belt fastened while operating the machine. Replace the seat belts when they become worn or broken.

Never wear a seat belt loosely or with slack in the belt system. Never wear the seat belt in a twisted condition or pinched between the seat structural members.




FIG. 11

FIG. 12: When using the instructor seat (1), securely fasten the seat belt (2). The instructor seat is to be used only to train new operators or diagnose a problem. The instructor seat is only intended for short periods of use. Extra riders, especially children, are not permitted on the machine.

When the instructor seat is used the machine must be driven at a slower speed and on level ground. Avoid quick starts, stops, and sharp turns. Avoid driving on highways or public roads.




FIG. 12

Shield and Guards

FIG. 13: All shields and guards must be in the correct operating position and in good condition.




FIG. 13

FIG. 14: Do not operate the machine with the drive shaft shields open or removed. Entanglement in rotating drive shafts can cause serious injury or death. Stay clear of rotating components.

Make sure rotating guards turn freely.



FIG. 14

Exhaust Warning

FIG. 15: Never operate the engine in a closed building unless the exhaust is vented outside.




FIG. 15

Flying Debris

FIG. 16: Never stand near the machine during operation. Debris can be thrown from the machine during operation possibly resulting in injury.




FIG. 16

Handrails

FIG. 17: Face the ladder and use the handrails when getting on or off the machine.



FIG. 17

01-8 4283559M1

TRAVEL ON PUBLIC ROADS

FIG. 18: Make sure you understand the speed, brakes, steering, stability, and load characteristics of this machine before you travel on public roads.

Use good judgment when traveling on public roads. Maintain complete control of the machine at all times. Never coast down hills.

The maximum speed of farm equipment is governed by local regulations. Adjust travel speed to maintain control at all times. See Specifications for the maximum speed for this machine.

Familiarize yourself with and obey all road regulations that apply to your machine. Consult your local law enforcement agency for local regulations regarding movement of farm equipment on public roads. Use headlights, flashing warning lights, taillights and turn signals, day and night, unless prohibited by local law.

Make sure all the flashers are operating prior to driving on the road. Make sure reflectors are correctly installed, in good condition, and wiped clean. Make sure the Slow Moving Vehicle (SMV) emblem is clean, visible, and correctly mounted on the rear of the machine.

Always travel with the header as low as possible. Do not drive with header up and the lift cylinder stops in the locked position. See Cylinder Stops in this section for more information.

Lock brake pedals together with the locking strap so that both front wheel brakes will be applied at the same time.

Be aware of other traffic on the road. Keep well over to your own side of the road and pull over, whenever possible, to let faster traffic pass.

Be aware of the overall width, length, height, and weight of the machine. Be careful when transporting the machine on narrow roads and across narrow bridges.

FIG. 19: Watch for overhead wires and other obstructions. Avoid contact with electrical power lines. Contact with electrical power lines can cause electrical shock, resulting in very serious injury or death.




FIG. 18




FIG. 19

MAINTENANCE

General Information

FIG. 20: Before doing any unplugging, lubricating, servicing, cleaning, or adjusting:

- Park the machine on a solid level surface.
- Make sure the transmission is in gear and apply the parking brake.
- · Stop the engine and take the key with you.
- Look and Listen! Make sure all moving parts have stopped.
- Put blocks in front of and behind the wheels of the machine before working on or under the machine.

Do not pull crop or any other object from the machine while the machine engine is running. Moving parts can pull you in faster than you can move away.

Check all nuts and bolts periodically for tightness, especially wheel mounting hardware.

Do not attempt to service or adjust the machine until all moving parts have stopped.

After unplugging, lubricating, servicing, cleaning, or adjusting the machine make sure all tools and equipment have been removed.

Make sure electrical connectors are clean and free of dirt or grease before connecting.

Check for loose, broken, missing, or damaged parts. Make sure the machine is in good repair. Make sure all guards and shields are in position.

FIG. 21: Never service, check or adjust drive chains or belts while the engine is running.




FIG. 20



FIG. 21

01-10 4283559M1


FIG. 22: Do not operate the machine with the drive shafts shields open or removed. Entanglement in rotating drive shafts can cause serious injury or death.

Stay clear of rotating components.

Make sure rotating guards turn freely.

A loose yoke can slip off a shaft and result in injury to persons or damage to the machine.


When installing a quick disconnect yoke, the spring activated locking pins must slide freely and be seated in the groove on the shaft. Pull on the driveline to make sure the quick disconnect yoke can not be pulled off the shaft.



When it is necessary for the header or the reel to be in the raised position, raise the header or reel all the way and engage the cylinder stops. See Cylinder Stops in this section for more information.



WARNING: Always install the header lift cylinder stops when working near the header. Do not rely on the hydraulic system to keep the header raised. A sudden loss of hydraulic pressure could cause the header to lower unexpectedly.



Keep all access areas clean and free of obstructions.



FIG. 22




FIG. 23



FIG. 24

Fire Prevention and First Aid

FIG. 25: Be prepared for emergencies.

Keep a first aid kit handy for treatment of minor cuts and scratches.

Due to the nature of the crops this machine will operate in, the risk of fire is of concern.

Always carry one or more fire extinguishers of the correct type. Check fire extinguishers regularly as instructed by the manufacturer. Make sure fire extinguishers are properly charged and in operating condition.

Use a water type fire extinguisher or other water source for a fire in crop.

Know how to operate the fire extinguisher before operating the machine.

For fires involving anything other than crop, such as oil or electrical components, use a dry chemical fire extinguisher with an ABC rating.

Mount fire extinguishers within easy reach of where fires can occur.

Frequently remove accumulated crop material from the machine and check for overheated components. Check the machine daily for any noises that are not normal. Such noises could indicate a failed component that can cause excess heat.

If any flame cutting, welding, or arc welding is to be done on the machine or attachments, make sure to clear any crop material or debris from around the area. Make sure the area below the work area is clear of any flammable material as falling molten metal or sparks can ignite the material

FIG. 26: If fire occurs stand upwind and away from smoke from the fire.




FIG. 25




FIG. 26

01-12 4283559M1

Thank you very much for your reading. Please Click Here. Then Get COMPLETE MANUAL. NO WAITING




NOTE:

If there is no response to click on the link above, please download the PDF document first and then click on it.

Checking for High Pressure Leaks

FIG. 27: Fluid leaking from the hydraulic system or the fuel injection system under high pressure can be very hard to see. The fluid can go into the skin causing serious injury.

Fluid injected into the skin must be surgically removed within a few hours. If not removed immediately, serious infection or reaction can develop. Go immediately to a doctor who knows about this type of injury.



Relieve all pressure before loosening any hydraulic lines. Relieve the pressure by lowering raised equipment, shutting off accumulator valve, if equipped, and shutting off the engine. Tighten all connections securely before applying pressure.




FIG. 27




FIG. 28

Engine Safety



CAUTION: See the engine Instruction Manual for other important engine safety information.

FIG. 29: Make sure all shields, guards and access doors are in place and properly closed before starting the engine.

Start the engine from the operator's seat only. Make sure all controls are in neutral and drives are disengaged.

Make sure all bystanders are clear of the machine before starting the engine.

Do not bypass the neutral start system. The neutral start system is designed to prevent starting the machine in gear. Any manual override of this system can cause death or serious injury.


Never connect booster cables to the starter terminals or short across the starter terminals.




FIG. 29

FIG. 30: The engine is equipped with an electric starting aid. Do not use aerosol starting fluid! Use of this fluid can cause an explosion resulting in possible severe injury or death.


Do not use aerosol starting fluid as a starting aid. The heaters in the intake manifold can cause the starting fluid to ignite resulting in an explosion. This explosion can cause death or very serious injury and damage to the engine.



LOOK AND LISTEN! Make sure all moving parts have stopped.



Always permit parts that contain hot fluid or gases to cool to the touch before handling or disconnecting.



Always permit the radiator to cool to the touch before removing the cap.




FIG. 30




FIG. 31



FIG. 32




FIG. 33

01-14 4283559M1

Adding Fuel

FIG. 34: Always stop the engine before adding fuel. Keep open flames and electrical sparks away from the area. Do not smoke while adding fuel.



FIG. 34

Diesel Exhaust Fluid Safety

FIG. 35: The Diesel Exhaust Fluid (DEF) is stored in the DEF storage tank (1).

Avoid all contact of DEF with eyes, skin and clothing.

DEF is classified as non-hazardous by the EPA.

DEF is very corrosive and must be handled with care. DEF must not contact any parts or containers made of aluminum.

In the event of spillage, rinse the area with water and wipe dry.

If large quantities of DEF is swallowed, see medical attention immediately. Do not induce vomiting unless indicated to do so by a medical professional. Do not give liquid to a person who is unconscious.

In case of contact with the eyes, rinse the eyes immediately under running water. In the event of irritation, seek medical attention.

In case of skin contact, rinse the area with water and remove contaminated clothing.

Prevent DEF from coming in contact with other chemicals.

Do not pour or wash DEF down drains.




FIG. 35